

ISONEM ISOTAPE TECHNICAL DATA SHEET

Product Name	: ISONEM ISOTAPE
Density (25°C, g/cm³)	: 1,45 ± 0.10
Adhesion (N/cm²)	: 25 - 35
Cold Temperature Flexibility	: No cracking or loss of adhesion
Vapor Transmission Rate	: 0,15 g/m ² /24 h/mm
Elongation (%)	: 600 - 800
Compressive strength	: 70 Psi, application from within 15 Psi, application from outside
Color	: Black
Packaging	: 1.5 m roll, 12 pieces/parcel

USAGE AREAS

- Roof leaks, gutters,
- Taps,
- Boats, skis,
- Personal watercraft, canoes,
- Outdoor equipment,
- Caravans,
- PVC, sanitary pipeworks
- Sprinkler systems,
- Pools and spas,
- Windows, doors, walls,
- Ventilation ducts

APPLICATION INFORMATION

Clean the surface which is the water leak and stick it. In deep water leaks, the tape is brought the pasty and the damaged area is filled. Then its surrounding is cleaned and the tape is stuck. It is disposable. When it is removed from the surface, it is not used again. Do not apply at temperatures above 60°C.

FEATURES AND BENEFITS

ISONEM ISOTAPE has been created with a special formula. It can be applied even underwater whether hot or cold, wet or dry. It creates a highly strong, flexible and water-repellent barrier by sealing water, air, and moisture. ISONEM ISOTAPE is UV-resistant, environmentally friendly, VOC-free and has a wide temperature range that can be used in extreme weather conditions. It can close almost everything like large holes, cracks, gaps, and leaks.

- *It is dimensions 150cm x 5 cm.*
- *It can make coating including underwater.*
- *It can be cut and used in pieces.*
- *It is very powerful and multi-purpose.*