

TECHNICAL DATA SHEET

ISONEM NANO-CLEAN SPRAY

(Surface Cleaner)

Product Description

SURFACE CLEANER, It is a general-purpose cleaner developed for cleaning and removing the joint remnants on tiles rapidly and effectively in all kinds of ceramic applications.

Usage Areas

- Before painting, it is used for the preparation of metals and removal of the oil, dirt, and rust on metal surfaces.
- It removes the dirt in bathrooms, kitchens, and rooms without damaging the stainless steel and plastic surfaces.
- It should only be applied on stone, porcelain, ceramic, baked clay tiles as a joint cleaner.

Application Procedure

- The product is applied directly to the surface to be cleaned. (Joints, stucco coatings, metal surfaces, parts being processed, etc.). Shake the product before application and spray on the surface from 20 – 30 cm away.
- It is expected to penetrate for a maximum of 2-3 minutes. The oil, dirt, rust, stain etc. are removed by wiping with a sponge or cloth. The approximate consumption amount is 150 - 200 mL /m².
- If dirt is difficult, the application should be repeated and scrubbed with a brush or similar material.
- The surface should be thoroughly rinsed with plenty of water. In the case of metal cleaning, the protective agent should be applied immediately after cleaning.
- Do not use together with other surface cleaning agents at the same time.

IMPORTANT

The equipment to which it is applied must be made of acid-resistant material. It is recommended to test the product in a small area. Take protective measures and wear glasses and gloves during application. The product is irritating to the eyes and skin. In case of contact with eyes, rinse immediately and seek medical advice.

Packaging & Storage

<u>Packaging</u>	: 0,3 L Spray bottle
<u>Storage temperature (°C)</u>	: 5 - 35 °C
<u>Shelf life</u>	: 24 months from date of production if stored in original, unopened, undamaged packages.
<u>Storage condition</u>	: Protect the package from direct sunlight and avoid storing it in high temperatures above 50°C.

ISONEM®

Boya ve Yalıtım Teknolojileri İnş. San. Tic. A.Ş.
Paint and Insulation Technologies Construction Industry Trade Inc.

Cleaning of Tools

Clean all tools and application equipment with clean water immediately after use.

Health and Safety Information

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.

ISONEM®

Boya ve Yalıtım Teknolojileri İnş. San. Tic. A.Ş.
Paint and Insulation Technologies Construction Industry Trade Inc.

Statement of Responsibility

The technical information and application advice given in this ISONEM Paint & Insulation Technologies publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.



ISONEM BOYA VE YALITIM TEKNOLOJİLERİ İNŞ. SAN. TİC. A.Ş.

Fabrika : İTOB OSB 10001 SK. NO:20 TEKELİ MENDERES İZMİR POSTA KODU : 35470 MENDERES VD. : 4810888223 TEL : 0 (232) 799 04 95 FAX : 0 (232) 437 01 33
WEB : www.isonem.com.tr E-MAIL : isonem@isonem.com.tr