


ISONEM[®] MAGNETIC PLASTER



Special Paints

Magnet Adhesive Plaster

ISONEM MAGNETIC PLASTER is a high-performance plaster which is waterbased, fast-drying, friction resistant, not color changing, and thanks to the magnetic metal in its structure, can hang pictures, posters, etc., having magnets on their backside without damaging paint. It can be hung things like pictures, posters to the wall or on a wooden surface without using a nail, tape, screw or glue. When **ISONEM WRITE & ERASE VARNISH** is applied on to it, an awesome combination is obtained, the wall becomes both writeable&erasable and magnet stickable. It is applied by mixing with water, does not smell, does not harm human health and environmental. **ISONEM MAGNETIC PLASTER** does not damage computer monitor, mobile phone, TV, credit card, ATM card even though it creates a magnetic field.

APPLICATION AREA

- Interior walls
- studios
- Schools
- conference rooms,
- Hospitals
- offices,
- Shopping centers

APPLICATION INFORMATION

The application surface must be smooth, firm and free from dust. **ISONEM MAGNETIC PLASTER** (18 kg) and 6.5 lt clean water are mixed homogeneously in a plastic container with a motorized mixer. The mixture is applied to a surface by troweling or spraying. The application is done as one or two layers and **ISONEM MAGNETIC PLASTER** applied with 1 mm thickness is spreaded and trowelled. After these processes, **ISONEM WRITE & ERASE VARNISH** or any interior paint can be applied. It should be waited for at least 24 hours for the paint application on **ISONEM MAGNETIC PLASTER**.

CONSUMPTION : 1 -2 kg/m²

(May vary depending on application surface and number of coats).

PACKAGING : 5 kg, 10 kg and 18 kg PE Bucket.

CONSUMPTION : 5 kg : 2,5 - 5 m²/1 bucket, 10 kg : 5 - 10 m²/1 bucket,

18 kg: 9 - 18 m²/1 bucket

COLOR : Black

STORAGE : 24 months in original, unopened package, cool and dry environment.

IMPORTANT
The surface should be protected from rain, water, mechanical loads and impacts for 24 hours during and after the application.

General Features



Magnetic Surface



A2 S1 d0
Fire Class



Do not contain harmful chemicals for environment and human health



No Odor



Application Conditions and Risks

Things to consider during and after the application

The application surfaces must be clean and free from dirt, oil, rust etc..

Applicable temperature

Between +5 and +35°C

Application Recommendation

Any interior wall paint can be applied on ISONEM Magnetic Plaster application. We recommend ISONEM Write & Erase Varnish application on ISONEM Magnetic Plaster application.



Surface Floor	Concrete	Marble, Granite	Raw wood	Tile & Ceramic	Membrane, Shingle etc.	Steel & Metal
Application	Vertical/Horizontal	X	Vertical/Horizontal	X	X	X
Surface Humidity	Dry	X	Dry	X	X	X
Application Tools	Trowel / Spraying	X	Trowel / Spraying	X	X	X
Primer Usage	X	X	X	X	X	X
Primer.Conspt	X	X	X	X	X	X
Product Usage	1 Layer	X	1 Layer	X	X	X
Product.Conspt	1 - 2 kg/m ²	X	1 - 2 kg/m ²	X	X	X
Betw.Two.Coats	X	X	X	X	X	X
Application	3 Days	X	3 Days	X	X	X



Finishing



The information given in this technical data sheet has been prepared according to our knowledge, experiment results, and experiences. The correct and successful implementation of our products is completely beyond our control and responsibility. For this reason, our responsibility is limited to the quality of our product only, and this manual overrides all previous technical statements, descriptions and label information.

" Our products are not classified by Biocidal Products Regulation "